

UB SpringLamp® Specifications

UB SpringLamp® Compact Fluorescent


- NPF, 10,000 hours average rated life

Item #	Wattage	Incandescent Wattage Comparison	Initial Lumens	Color Temperature	Input Line Current	M.O.L. (inches)	Diameter (inches)	Power Factor
AM094 ★	9	40	600	2700°K	.15A	4.0	1.8	>.50
AM144 ★	14	60	900	2700°K	.20A	4.4	1.8	>.50
AM204 ★	20	75	1200	2700°K	.31A	4.6	2.3	>.50
AM234 ★	23	90	1600	2700°K	.38A	4.9	2.3	>.50
AM274 ★	27	100	1750	2700°K	.46A	5.5	2.4	>.50

★ = Compact



27 Watts



23 Watts



20 Watts



14 Watts Mini



9 Watts Mini

Features and Benefits:

- Long life, 10,000 hour average rated life
- Lasts 7 years, based on 4 hours use per day
- Lasts 10-13 times longer than incandescent
- Replace less often, ideal for hard to reach places
- Lower maintenance costs for lamp replacements
- Saves up to 75% in energy costs compared to similar light output incandescent lamps
- 2700°K color temperature closest to incandescent light
- Quick run-up time
- Medium base and compact height fits anywhere a standard incandescent fits
- Instant start, flicker free
- End of Life logic guards against violent failures
- World class phosphor insures high lumen output and excellent lumen maintenance
- Up to 23 watts approved for enclosed fixtures

Applications:

Use anywhere a standard incandescent is used.
Perfect for: Table Lamps, Floor Lamps, Ceiling Fixtures, Wall Sconces, Closet Lights and Desk Lamps

Specifications (at full brightness)

End of Life Protection -----	Yes
Ballast Type -----	Electronic
Starting Method -----	Modified Rapid Start
Input Line Voltage -----	120VAC
Input Line Frequency -----	50/60HZ
Lamp Life (rated) -----	10,000 Hours
Color Temperature -----	2700°K
Color Rendering Index -----	82
Min. Starting Temperature -----	-20 ° F
Max. Operating Temperature -----	160 ° F
U.L. / C.U.L. Listed -----	Yes
FCC Compliance -----	Part 18, Subpart C
Lamp Operating Frequency -----	45 KHZ
Lamp Current Crest Factor -----	< 1.60
Max. Open Circuit Voltage -----	600V
Total Harmonic Distortion (NPF) -	< 150%



ISO 9002
CERTIFIED

12 MONTH
WARRANTY